



## Deutz Fahr 5G Series

5105.4G HD (102hp) – 5115.4G (109hp)

### Engine:

- Powered by liquid cooled four cylinder turbocharged and intercooled engine.
- 150L fuel tank
- Individual Bosch injector pumps
- Powercore air filter with dust injector
- 5 or 6hp power boost
- Torque 408Nm @1600rpm
- Isolator under bonnet
- Slide out air con radiator – easy to clean
- Independent braking

### Transmission:

- Wet clutch powershuttle
- Heavy duty rear axle
- 4 wheel independent braking
- Front & rear diff lock
- Comfort Clutch
- Stop & Go function on 5115.4G
- 40km/h road speed
- Transmission high & low
- Heavy duty Powertrain with two gear box configurations;  
**5105.4G HD** – 40/40 gears with 2 speed powershift  
**5115.4G HD** – 60/60 gears with 3 speed powershift  
Includes creeper



### Operator Station:

- Roomy, quiet and ergonomic air-conditioned cabin
- Ergonomic controls
- Air suspension seat
- DeClutch button
- Analogue dash
- Front, rear and cabin work lights
- 5115.4G has extra work lights on Cab posts

### Front End Loader & Linkage:

- Euro hitch implement attachment
- 3 sets of remotes – 1 Kick out/1 Detent/1 Float
- 3600kg (5105.4G) - 4900kg (5115.4G) rear lift capacity
- Hook in's
- Rear linkage up & down and PTO controls – both sides of tractor

### Wheel Dimensions:

- **5105.4G** 420/70R24 Front – 480/70R34 Rear
- **5115.4G** 440/65R28 Front – 540/65R38 Rear

